

Cristal-Flo™ II

Sand Filters for Inground Pools
by Sta-Rite®



Press, twist and relax

You won't burn many calories maintaining the Sta-Rite® Cristal-Flo™ II sand filter: A little two-way wrist action on the control valve puts Cristal-Flo II to work cleaning itself. And this is one workout routine you won't have to do very often. Through innovative engineering, the filter's dirt-handling capacity is maximized, which extends the time between cleanings (backwashing). But best of all, the Cristal-Flo II promises to make your pool water sparkle in the sun and shimmer in the moonlight.

- Tank shape, internal component design and even hydraulic flow have been engineered to maximize filter performance and extend the time between cleanings.

- Easy maintenance and outstanding water quality have made Cristal-Flo II the top choice among pool professionals and pool owners alike.
- One-piece tank is constructed of high-density thermoplastic resin, which ensures many years of service, no matter how harsh the climate.
- Sta-Rite innovation takes sand filtration technology to the next level by delivering superior quality, performance and value at an affordable price.

Exercise your good judgment and let the Cristal-Flo II sand filter do the work for you.

Cristal-Flo™ II Sand Pool Filters



Six-function multi-port valve for easy control of all filter functions

- Filter
- Backwash
- Rinse
- Waste
- Closed
- Recirculate

One-piece thermoplastic tank for strength and corrosion resistance

Combination water and sand drain for easy service and winterizing



For all the right reasons

Sand is the most widely used filtration method for swimming pools. Convenience, low maintenance and water quality are the reasons for sand's popularity. The Cristal-Flo™ II filter is a time-tested favorite with pool owners due to its extended maintenance cycles, easy-to-operate control valve selector and outstanding water clarity. The biggest reason for installing Cristal-Flo II: the additional leisure time you'll spend enjoying your pool.

- Top-mount, 6-function, 1½" multi-port valve features a pressure gauge and manual air relief for optimum filtration efficiency.
- Internal design ensures that water is exposed to maximum sand surface area for superior filtration performance and efficient backwashing.
- New, larger capacity unit—CFII26—for even the largest pools.

Filter Performance

Model	For Pools up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Flow Rate GPM ¹	Valve	Sand Required (lbs.)
TOP-MOUNT FILTER					
CFIII5	16,800	1.2	35	1½" Multi-Port	100
CFIII9	19,200	1.9	40	1½" Multi-Port	150
CFII22	28,800	2.6	60	1½" Multi-Port	250
CFII24	33,600	3.2	70	1½" Multi-Port	300
CFII26	36,000	3.9	75	2" Multi-Port	350

¹ Use only #20 white quartz silica sand, size range .40-.55 mm; 12" to 15" sand bed depth required.

Operating Limits – Maximum continual operating pressure is 50 PSI for 24" and 26" tanks, 35 PSI for 20" and smaller; Maximum operating water temperature (internal filter) is 95°F (35°C).

One-year limited warranty. See warranty for details.

Available from:



Simply Smarter.

www.staritepool.com

Phone: 800-831-7133

pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products